

Aurora

Your Security
Our Focus

Series

960H Digital Video Recorder

800TVL(5MP Sensor) Auto Tracking Camera

700TVL High Resolution Camera



QR code for
Scan and View



Compatible with
Dropbox



**Front Panel Touch
Technology**




Login
My KGUARD

Push Notification



Auto Tracking Camera



800 TVL Auto Tracking Camera



800 TVL super high resolution, **WDR** function, and up to **30m/100ft** night vision in total darkness with intelligent auto tracking to allow you to focus on important people and objects. The camera can automatically detect moving objects in its field of view and focus on that part of the picture to make it become larger and clearer.



standard



intelligent auto tracking



With WDR



Without WDR

No network setup required

Easy connection to the internet via QR code

Only 3 simple steps to setup. Just plug the DVR into the internet, download the KViewQR app and use the device to scan the QR code on your DVR. Once the scan is complete, you can use your device right away.



Push Notification for your Smartphone and Tablet

The DVR supports push notification for your smartphone and tablet. Using motion technology to focus on important areas. If any moving object enters this area, your smartphone or tablet will activate push alarm to let you know that something happened.



Store Images on "Dropbox"

Traditional digital video recorders can only save images in their hard disks. Now KGUARD supports cloud service with Dropbox. This cloud storage allows users to have access to images at any time from anywhere making it easy to monitor and share in seconds. These images will be stored safely even if the DVR is stolen or damaged.



mykguard.com



We created mykguard.com to help users easy access from the Internet to monitor their home or business

KViewQR app

support free KViewQR app on iOS and Android system

Anywhere Anytime



for Android / iOS

Full HD Solution

Output
**Full HD
1080P**

960H
Recording Resolution



Front Panel Touch



HZ213A

(The auto tracking camera)



800
TVL

800 TVL super high resolution and 30m/100ft night vision in total darkness with intelligent auto tracking to allow you to focus on important people and objects



Digital wide dynamic range to eliminate shadows



The cameras have waterproof casings that are weather resistant for most areas



3.6mm fixed lens with 75 degrees viewing angle to monitor particular areas



HW307E



700
TVL

700 TVL high resolution and 20m/65ft night vision in total darkness for clearer video



The cameras have waterproof casings that are weather resistant for most areas



3.6mm fixed lens with 75 degrees viewing angle to monitor particular areas



DVR Specification

Model No.	AR421	AR821	AR1621
No. of Channel	4 Channels	8 Channels	16 Channels
Cloud			
Cloud Storage	Yes	Yes	Yes
Storage Mode	Schedule / Motion Detection	Schedule / Motion Detection	Schedule / Motion Detection
Video			
Video Format	NTSC / PAL	NTSC / PAL	NTSC / PAL
Video Input	4 BNC Inputs	8 BNC Inputs	16 BNC Inputs
Video Output	1 VGA, 1 BNC, 1 HDMI Outputs		
Video Output Resolution	1024x768, 1280x1024, 1366x768, 1440x900, 720p, 1080p	1024x768, 1280x1024, 1366x768, 1440x900, 720p, 1080p	1024x768, 1280x1024, 1366x768, 1440x900, 720p, 1080p
Audio			
Audio Input	4 RCA Inputs	8 RCA Inputs	2 RCA Inputs
Audio Output	1 RCA Output	1 RCA Output	1 RCA Output
Recording			
Video Compression	H.264	H.264	H.264
Recording Frame Rate			
D1-NTSC	120fps@CIF (352x240), 120fps@HD1 (704x240), 120fps@D1 (704x480)	240fps@CIF (360x240), 240fps@HD1 (720x240), 240fps@D1 (720x480)	480fps@CIF (360x240), 240fps@HD1 (720x240), 240fps@D1 (720x480)
D1-PAL	100fps@CIF (352x288), 100fps@HD1 (704x288), 100fps@D1 (704x576)	200fps@CIF (360x288), 200fps@HD1 (720x288), 200fps@D1 (720x576)	400fps@CIF (360x288), 192fps@HD1 (720x288), 192fps@D1 (720x576)
960H-NTSC	120fps@WCIF (480x240), 120fps@WHD1 (960x240), 120fps@WD1 (960x480)	240fps@WCIF (480x240), 88fps@WHD1 (960x240), 88fps@WD1 (960x480)	480fps@WCIF (480x240), 176fps@WHD1 (960x240), 176fps@WD1 (960x480)
960H-PAL	100fps@WCIF (480x288), 100fps@WHD1 (960x288), 100fps@WD1 (960x576)	200fps@WCIF (480x288), 72fps@WHD1 (960x288), 72fps@WD1 (960x576)	400fps@WCIF (480x288), 144fps@WHD1 (960x288), 144fps@WD1 (960x576)
Recording Mode	Always / Manual / Motion Detection / Schedule / Alarm	Always / Manual / Motion Detection / Schedule / Alarm	Always / Manual / Motion Detection / Schedule / Alarm
HDD Interface	1 SATA	1 SATA	1 SATA
HDD Support	Up to 2TB	Up to 2TB	Up to 2TB
Network			
Plug & Play	Yes	Yes	Yes
Network Interface	RJ45, 10M/100M	RJ45, 10M/100M	RJ45, 10M/100M
Network Type	DHCP, PPPoE, Static IP	DHCP, PPPoE, Static IP	DHCP, PPPoE, Static IP
Playback			
Local Playback	Max. 4 Channels Simultaneously	Max. 8 Channels Simultaneously	Max. 16 Channels Simultaneously
Playback Search	Time / Channel / Event	Time / Channel / Event	Time / Channel / Event
Playback Mode	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom
General			
PTZ Control	RS485 Built-In, supports PELCO-P & PELCO-D	RS485 Built-In, supports PELCO-P & PELCO-D	RS485 Built-In, supports PELCO-P & PELCO-D
E-SATA Port	No	No	Yes
Sensor IN & Alarm OUT Port	4-IN, 1-OUT	8-IN, 1-OUT	4-IN, 1-OUT
Backup Method	HDD, USB, Network	HDD, USB, Network	HDD, USB, Network
Power Supply	12V/2A	12V/2A	12V/2A
Operating Temperature (W/O HDD)	-10°C to 55°C (14°F to 131°F)	-10°C to 55°C (14°F to 131°F)	-10°C to 55°C (14°F to 131°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)	-20°C to 70°C (-4°F to 158°F)	-20°C to 70°C (-4°F to 158°F)
Working Humidity	10%~90%	10%~90%	10%~90%
Dimension (LxWxH) in mm	315x230x40	315x230x40	315x230x40

Camera Specification



Model Name	HZ213A
Video	
Image Sensor	5M Pixels High Quality CMOS Image Sensor
Horizontal Resolution	800TVL
Electronics Shutter	NTSC 1/60-1/100,000(sec) PAL 1/50-1/100,000(sec)
Lens	3.6mm Megapixel Fixed
Viewing Angle	75 Degrees to 25 Degrees
Video Output	1.0VP-P, 75Ω
S/N Ratio	More than 48dB (AGC OFF)
Day / Night Mode	Color during day / switches to B&W at night
Minimum Illumination	While Infrared LED on "0" lux
Gain Control	Auto
Backlight Compensation	Auto

Night Vision	
Night Vision Distance	30m / 98ft
Illumination	Infrared LED
Infra-Red Wavelength	850nm
Infra-Red LED Life	10,000hrs

General	
WDR	Smart WDR
Auto Tracking	Yes
Indoor / Outdoor	Weatherproof (Both)
Operating Temperature	-10~50°C / 14~122°F
Storage Temperature	-20~70°C / -4~158°F
Body Construction	Aluminum
Dimensions-	72x63x167.5mm
Camera with Stand (WxDxH)	
Weight-Camera with Stand	350g



Model Name	HW307E
Video	
Image Sensor	1/3" SHARP Color CCD
Horizontal Resolution	700TVL
Electronics Shutter	NTSC 1/60-1/120,000(sec) PAL 1/50-1/120,000(sec)
Lens	3.6mm
Viewing Angle	75 Degrees
Video Output	1.0VP-P, 75Ω
S/N Ratio	More than 52dB (AGC OFF)
Day / Night Mode	Color during day / switches to B&W at night
Minimum Illumination	While Infrared LED on "0" lux
Gain Control	Auto
Backlight Compensation	Auto

Night Vision	
Night Vision Distance	20m / 65ft
Illumination	Infrared LED
Infra-Red Wavelength	850nm
Infra-Red LED Life	10,000hrs

General	
Indoor / Outdoor	Weatherproof (Both)
Operating Temperature	-10~50°C / 14~122°F
Storage Temperature	-20~70°C / -4~158°F
Body Construction	Aluminum
Dimensions-	164x58x58mm
Camera with Stand (WxDxH)	
Weight-Camera with Stand	235g

Model Options:

AR421-HZ213A+3HW307E



AR821-HZ213A+3HW307E



AR821-2HZ213A+6HW307E



AR1621-2HZ213A+6HW307E



What's in the box?

 Standalone DVR	 Camera	 Remote Control	 USB Mouse
 Software CD	 Slim Cable (18m / 60ft)	 4 Way Split Cable	 Power Adapter (12V)
 HDMI Cable	 Ethernet Cable	 Quick Installation Guide	 Warranty Card



KGUARD INFORMATION CO., LTD. (Headquarters)

Address: 4F, No.113, Jian 2nd Rd., Jhonghe Dist., New Taipei City 23585 ,Taiwan (R.O.C.)

TEL: +886-2-8228-6080

FAX: +886-2-8221-6857

Technical Support: support@kguardsecurity.com

Sales Inquiry: sales@kguardsecurity.com



www.kguardsecurity.com



www.facebook.com/KguardGlobal



www.youtube.com/user/KGUARDSECURITY

Copyright © 2013 KGUARD INFORMATION CO., LTD. All Rights Reserved. KGUARD Security is trademark of KGUARD INFORMATION CO., LTD.
Product features & specifications are subject to change without notice
All pictures are for your reference only

Authorized KGUARD Security Distributor