

# All-IN-One

Surveillance Combo Kit

4/8/16 Channel Digital Video Recorder with HDMI output  
600 TVL High Resolution Cameras

Your Security  
Our Focus

HD recording resolution  
quality is better than D1

**960H**

Output

**Full HD  
1080P**



# Why CHOOSE KGUARD 960H All-In-One Combo kit

## 960H Super resolution to provide you perfect quality images

KGUARD provides a new digital video recorder with 960H recording resolution. 960H recording resolution gives you HD quality videos and images with 600TVL cameras. Its resolution is 34% higher than standard D1 resolution and 500% higher than CIF resolution. You don't need to worry about the video or image becoming unclear or losing important information.



All Pictures are Sample Only

## All-In-One Quick DIY Setup

All devices and accessories that you need to install a complete surveillance system are included in One Box. No more spending time and money selecting individual devices. Just open the box and install your own surveillance solution to save labor and maintenance cost

## Supports HDMI Output

Each 960H Series DVR is equipped with Full HD output which is displayed at 1080p standard, providing you with excellent HD videos and images on HDTV at home or at work.



CIF 352X240 pixels



D1 704X480 pixels



960H 960X480 pixels



**HDMI**™  
HIGH DEFINITION MULTIMEDIA INTERFACE



All Pictures are Sample Only



H.264 compression latest recording technology



Live view, playback, and event alarm without missing any important information



960H HD recording resolution quality is better than D1




Advanced time bar for easy control and playback



Full HD output with 1080P display standard for connection to HDTV



Advanced motion schedule can manage email alerts easily



**KGUARD Fulcolor** to provide excellent colorful images



Night vision up to 20m/65ft in total darkness



6mm fixed lens with 40 degrees viewing angle to monitor particular areas



Waterproof case to protect the camera and survive rainy days




600 TVL high resolution to make video clearer



Free "Kview" allows remote monitoring on your smartphones and tablets

### Free KView App Series for Remote Monitoring Anywhere

Available for mobile devices, Mac and PC computers can download this App to monitor your home, office, children, or pets on your mobile devices while you are traveling on business or on vacation



# DVR Specification

Model No.	BR421	BR821	BR1621
No. of Channel	4 Channels	8 Channels	16 Channels
<b>Video</b>			
Video Format	NTSC / PAL	NTSC / PAL	NTSC / PAL
Video Input	4 BNC Inputs	8 BNC Inputs	16 BNC Inputs
Video Output	1 VGA, 1 BNC, 1 HDMI Outputs	1 VGA, 1 BNC, 1 HDMI Outputs	1 VGA, 1 BNC, 1 HDMI Outputs
Video Output Resolution	VGA: 800x600, 1024x768, 1280x1024, 1440x900, 1920x1080 HDMI: 1080p	VGA: 800x600, 1024x768, 1280x1024, 1440x900, 1920x1080 HDMI: 1080p	VGA: 800x600, 1024x768, 1280x1024, 1440x900, 1920x1080 HDMI: 1080p
<b>Audio</b>			
Audio Input	2 RCA Inputs	2 RCA Inputs	4 RCA Inputs
Audio Output	1 RCA Output	1 RCA Output	1 RCA Output
<b>Recording</b>			
Video Compression	H.264	H.264	H.264
Recording Frame Rate			
D1-NTSC	120fps@CIF (360×240)	240fps@CIF (360×240)	480fps@CIF (360×240)
	120fps@HD1 (720x240)	240fps@HD1 (720x240)	240fps@HD1 (720x240)
	120fps@D1 (720x480)	240fps@D1 (720x480)	240fps@D1 (720x480)
D1-PAL	100fps@CIF (360×288)	200fps@CIF (360×288)	400fps@CIF (360×288)
	100fps@HD1 (720x288)	200fps@HD1 (720x288)	192fps@HD1 (720x288)
	100fps@D1 (720x576)	200fps@D1 (720x576)	192fps@D1 (720x576)
960H-NTSC	120fps@WCIF (480×240)	240fps@WCIF (480×240)	480fps@WCIF (480×240)
	120fps@WHD1 (960×240)	88fps@WHD1 (960×240)	176fps@WHD1 (960×240)
	120fps@WD1 (960×480)	88fps@WD1 (960×480)	176fps@WD1 (960×480)
960H-PAL	100fps@WCIF (480×288)	200fps@WCIF (480×288)	400fps@WCIF (480×288)
	100fps@WHD1 (960×288)	72fps@WHD1 (960×288)	144fps@WHD1 (960×288)
	100fps@WD1 (960×576)	72fps@WD1 (960×576)	144fps@WD1 (960×576)
Recording Mode	Always / Manual / Motion Detection / Schedule	Always / Manual / Motion Detection / Schedule	Always / Manual / Motion Detection / Schedule / Sensor / Alarm
HDD Interface	1 SATA	1 SATA	2 SATA
HDD Support	Up to 2TB	Up to 2TB	Up to 2TB
<b>Network</b>			
Network Interface	RJ45, 10M/100M	RJ45, 10M/100M	RJ45, 10M/100M
Network Type	DHCP, PPPoE, Static IP	DHCP, PPPoE, Static IP	DHCP, PPPoE, Static IP
<b>Playback</b>			
Local Playback	Max. 4 Channels Simultaneously	Max. 8 Channels Simultaneously	Max. 16 Channels Simultaneously
Playback Search	Date & Time / Event List / Time Bar	Date & Time / Event List / Time Bar	Date & Time / Event List / Time Bar
Playback Mode	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom	Play, Fast Forward, Fast Rewind, Slow Motion, Zoom
<b>General</b>			
PTZ Control	RS485 Built-In, supports PELCO-P & PELCO-D	RS485 Built-In, supports PELCO-P & PELCO-D	RS485 Built-In, supports PELCO-P & PELCO-D
Sensor & Alarm I/O Port	No	No	Yes
IR Extender Port	No	No	Yes
Backup Method	HDD, USB, Network	HDD, USB, Network	HDD, USB, Network
Power Supply	12V/2A	12V/2A	12V/5A
Operating Temperature (W/O HDD)	-10°C to 50°C ( 14°F to 122°F )	-10°C to 50°C ( 14°F to 122°F )	-10°C to 50°C ( 14°F to 122°F )
Storage Temperature	-20°C to 70°C ( -4°F to 158°F )	-20°C to 70°C ( -4°F to 158°F )	-20°C to 70°C ( -4°F to 158°F )
Dimension (WxDxH) in mm	305x230x55	305x230x55	385x335x55

## Camera Specification

<b>Video</b>	
Image Sensor	KGUARD Fulcolor
Pixels	728(H) x 560(V)
Electronics Shutter	NTSC 1/60-1/100,000(sec) PAL 1/50-1/100,000(sec)
Horizontal Resolution	600 TVL
Lens	6mm Fixed
Viewing Angle	40 Degrees
Video Output	1.0VP-P, 75Ω
S/N Ratio	More than 48dB (AGC OFF)
Day / Night Mode	Color during day / switches to B&W at night
Minimum Illumination	While Infrared LED ON "0" lux
Gain Control	Auto
Backlight Compensation	Auto
<b>Night Vision</b>	
Night Vision Distance	20m / 65ft
Illumination	Infrared LED
Infra-Red Wavelength	850nm
Infra-Red LED Life	10,000hrs
<b>General</b>	
Indoor / Outdoor	Weatherproof (Both)
Operating Temperature	-10°C~50°C (14°F~122°F)
Storage Temperature	-20°C~70°C (-4°F~158°F)
Body Construction	Aluminum
Dimensions-Camera with Stand	182x73x74mm / 7.2x2.9x2.9" (WxDxH)
Weight - Camera with Stand	260g / 0.57lbs

## Model Options:

 **BR421-4HW227D**



 **BR821-4HW227D**



 **BR821-8HW227D**



 **BR1621-8HW227D**



## What's in the box?



Standalone  
DVR



Camera



Remote Control



USB Mouse



Software CD



Slim Cable  
(18m / 60ft)



4 Way  
Split Cable



Power Adapter  
(12V)



HDMI Cable



Ethernet Cable



Quick  
Installation Guide



Warranty Card



*"Your security, our focus"*

*All products come with a one-year warranty for our customers.*

*We have our experienced technical support team to answer any questions for more information, please visit KGUARD's website: [www.kguardsecurity.com](http://www.kguardsecurity.com)*



**KGUARD INFORMATION CO., LTD. (Headquarters)**

Address: 4F, No.113, Jian 2nd Rd., Jhonghe Dist., New Taipei City 23585 ,Taiwan (R.O.C.)

TEL: +886-2-8228-6080

FAX: +886-2-8221-6857

Technical Support: [support@kguardsecurity.com](mailto:support@kguardsecurity.com)

Sales Inquiry: [sales@kguardsecurity.com](mailto:sales@kguardsecurity.com)

Authorized KGUARD Security Distributor