







Entry Level Affordable prices Professional Level

960P HD IP Cameras

960P (1280x960,1.3M) High resolution cameras allow you to identify a license plate number or a person's face

D1(0.3Mega Pixel)



960P(1.3Mega Pixel)



CIF(0.08Mega Pixel)



The picture is under ideal conditions(almost under 6m). Actual range and clarity may vary depending on scene/object reflection and camera application

POE-Connect Without Limitation



The outdoor IP Camera has built in Power over Ethernet(POE) that allows a single cable to provide electrical power and data transaction.



Easy Connection to The Internet Via QR Code

Only 3 simple steps to setup. Just plug the NVR into the internet, download the "New KView" app and use the device to scan the QR code on your NVR. Once the scan is complete, you can use your device right away.

- **▼No network setup required** DHCP mode
- **¥**Easy connection to internet via QR code







Store Images on "Dropbox"

The NVR supports cloud service with Dropbox. This cloud storage allows users to have access to images at any time from anywhere making it easy to monitor and share in seconds. These images will be stored safely even if the NVR is stolen or damaged.



Support HDMI Output

The NVR is equipped with Full HD output which is displayed at 1080p standard, providing you with excellent HD videos and images on HDTV at home or at work

1920 Pixels





Day & Night

IPB-200Night vision up to

Night vision up to 30m/98ft in total darkness





1080 Pixels

IPB=100





3.6mm lens with 75 degree viewing angle to monitor particular areas



Night vision up to 20m/65ft in total darkness



960P (1280x960,1.3M) High resolution cameras allow you to identify license plates or person's faces



Support integrated Power Over Ethernet (PoE) that allows a single cable to provide electrical power and data transaction.



Weather proof case to protect the camera and survive rainy days

IPB-200





6mm lens with 45 degree viewing angle to monitor particular areas



Night vision up to 30m/98ft in total darkness



960P (1280x960,1.3M) High resolution cameras allow you to identify license plates or person's faces



Support integrated Power Over Ethernet (PoE) that allows a single cable to provide electrical power and data transaction.



Weather proof case to protect the camera and survive rainy days

New KView

Support free New KView app on most popular device system





Anywhere Anytime



App Store

NVR Specification NVR MR-400 Cloud Cloud Storage Yes Schedule / Motion Detection Storage Mode Video Video Input 4 LAN ports Video Output 1 VGA & 1 HDMI Outputs Video Output Resolution 800x600, 1024x768, 1280x1024, 1440x900, 1920x1080 **Audio** G.711 Audio Compression **Audio Output** 1 RCA output Recording Video Compression H.264 4 x 30fps @ 720p Recording Resolution Recording Mode Manual / Always / Schedule / Motion Detection / Alarm / Remote Recording 1 SATA **HDD** Interface **HDD Support** Up to 4TB **Network** Network Interface 1 WAN port **Network Protocol** DHCP, PPPoE, Static IP IE 8.0 or above & Safari **Browser Support Playback** Local Playback 4 x 30fps @ 720p Remote Playback 4 channels simultaneously via broswers Time & Date, Alarm, Motion Detection Playback Search

Playback Mode Play, Fast Forward, Fast Rewind, Slow, Zoom

General

IR Extender Port

Sensor IN & Alarm OUT Port

Trigger Event

Backup Method

Power Consumption (W/O HDD)

Power Supply

Camera Power Supply over PoE

Operating Temperature (W/O HDD)

Working Humidity

Dimension (LxWxH)

Yes

4-IN. 1-OUT

Recording, Alarm Out, E-mail, Buzzer, Full Screen

USB Flash Drive, USB HDD, Network

≤15W

DC 19V/4A

Yes

 0° C to 55° C (32° F to 131° F)

10%~90%

300×220×47mm

^{*} Trademarks are properties of their respective owners.

Specification is subject to changes without prior notice.

Camera Specification

Camera	IPB-100
Image Sensor	1/3" Mega Pixel CMOS Sensor
	with IR Cut Filter
Max. Resolution	1280(H) x 960(V)
Lens	3.6mm fixed, F1.2

Viewing Angle 75°

20m / 65ft Night Vision

Minimum Illumination While Infrared LED on "0" lux

Day Mode Color during day

Night Mode switches to B&W at night

Electronics Shutter $1/3 \sim 1/10,000 \text{ (sec)}$

Waterproof **IP66**

Operating Temperature $-10 \,^{\circ}\text{C} \sim 60 \,^{\circ}\text{C} (14 \,^{\circ}\text{F} \sim 140 \,^{\circ}\text{F})$

Power Supply 12 VDC ± 10%, PoE

Dimensions 150x63x61mm

Weight 420g

Model Options:





MR-4020











Camera	IPB-200
mage Sensor	1/3" Mega Pixel CMOS Sensor
	with IR Cut Filter
Max. Resolution	1280(H) x 960(V)
_ens	6mm fixed, F1.2

Viewing Angle 45°

30m / 98ft Night Vision

Minimum Illumination While Infrared LED on "0" lux

Day Mode Color during day

Night Mode switches to B&W at night

Electronics Shutter $1/3 \sim 1/10,000 \text{ (sec)}$

Waterproof **IP66**

Operating Temperature -10 °C ~ 60 °C (14°F ~ 140°F)

Power Supply 12 VDC ± 10%, PoE

Dimensions 150x63x61mm

Weight 420g

What's in the box?



Standalone **NVR**



Camera



Remote Control



15M/30M PoE cable



1.8M Ethernet Cable



HDMI Cable



USB Mouse





Software CD



Power Adapter (19V4A)



Quick Installation Guide



Warranty Card



KGUARD INFORMATION CO., LTD. (Headquarters)

Address: 4F, No.113, Jian 2nd Rd., Jhonghe Dist., New Taipei City 23585, Taiwan (R.O.C.)

TEL: +886-2-8228-6080

FAX: +886-2-8221-6857

Technical Support: support@kguardsecurity.com Sales Inquiry: sales@kguardsecurity.com

www.kguardsecurity.com

www.facebook.com/KguardGlobal

www.youtube.com/user/KGUARDSECURITY

Authorized KGUARD Security Distributor